

# DSP-10

## Genset Multi-Function Display Module

### Features

First and only Multi-function Display Module specially designed for generator set.

Three sets four Digits High illumination LED Suitable for Outdoor use

Microprocessor Based Design

Full Phase AC Voltage RMS value Display

Full Phase with Load RMS value Display

AC Input Frequency Display

DC Supply Voltage Display

Engine Operating Time Display

All values can be programmed according to user's actual demand to be cyclic displayed

Compact, Anti-shock, Easy installation

DIN rail terminal for easy connection

Four adjustable Voltage and Current Push Buttons


Five Dip Switches For Specification Setting



### Specifications

DC Supply	DC Voltage 9 ~ 36 VDC (12V, 24V)
Alternator Input Range	AC Voltage 10 ~ 500 VAC
	Current 0 ~ 3000 Amp
	Frequency 50 / 60 Hz
Rated CT Capacity	Above 2.5VA
CT Secondary Ratio	5A
Power Consumption	Under 5VA
Operating Temperature	-20 ~ 70 °
Relative Humidity	Under 90%
Dimension	H * W * D = 72 * 72 * 50 mm
Weight	100 gram

### Mechanical Specifications (mm)



Cut-Out: 66.0±0.5 mm × 66.0±0.5 mm