

# GCU-10 KIT

## Auto Start Generator Control & Protection Panel

### Features

- Modular design · Quick installation · Simplify wiring and Save labor cost
- Waterproof front panel with Anti-UV protection
- Integrated microprocessor based design
- LED graphic interface for generator status and fault alarms
- High illumination LED displays suitable for outdoor use
- Three phase AC power parameters - V(RMS) · A(RMS) and Hz
- Operating hours and DC battery voltage display
- Programmable for cycle-mode or fix-mode displays
- Built-in relay module ready with fuses and power relays



### GCU-10 Protection & Alarm Indicators

Fail to Start	Over & Under Speed
High Water Temperature	Emergency Stop
Low Oil Pressure	Low Battery Voltage

### DSP-10 Displayed Parameter

AC Voltage V(RMS)	Operating hours (Hr)
Load Current A(RMS)	Battery Voltage (Vdc)
Frequency (Hz)	

### Specifications

<b>DC Supply</b>	12V or 24V
<b>Alternator Input Range</b>	GCU-10 : 5 - 300 Vac 50/60 Hz DSP-10 : 10 - 500 Vac 50/60 Hz
<b>Power Consumption</b>	GCU-10 : less than 3 watts DSP-10 : less than 2 watts
<b>Rated CT Capacity</b>	Above 2.5 VA
<b>CT Secondary Ratio</b>	5A

### Output Capacity

<b>Start Signal</b>	35 A @ 12/24 VDC
<b>Fuel Solenoid signal</b>	35 A @ 12/24 VDC
<b>Pre-Heat</b>	35 A @ 12/24 VDC
<b>Accessory - ON</b>	5 A @ 12/24 VDC
<b>Idle Control</b>	5 A @ 12/24 VDC

### Environment

<b>Operating Temperature</b>	-20°C to +70°C
<b>Storage Temperature</b>	-35°C to +85°C
<b>Relative Humidity</b>	Max. 90%

### Physical Specifications

<b>Panel Cut-Out</b>	66.0 x 66.0 +/-0.5 mm
<b>Dimension</b>	72.0 (H) x 72.0 (W) x 50.0 (D) mm
<b>Weight</b>	1.5 Kg +/-2%

### Mechanical Specifications

